Electrical Engineering in Japan

Subject Index to Volume 113, 1993

Ablation arc: **1**, 1
Ablation drag: **1**, 10
AC exciting synchronous generator: **1**, 70
AC superconducting stranded conductor: **4**, 25
Acceleration control: **5**, 102
Accelerator: **8**, 136
AC/DC system: **2**, 40
Active filter: **3**, 135
Adjustable speed hydroelectric power generation: **1**, 70
AE sensor: **8**, 73
Air-gap flux: **4**, 101; **5**, 35
Alkali metal **3**: 45
β″-Alumina: **3**, 46
Anti-resonance: **2**, 91
Application: **2**, 13
Approximation of magnetic characteristics: **6**, 1
Arc voltage **3**: 27
Arcing: **2**, 53
Arcing in polyethelene: **1**, 1
Armature: **1**, 10
Armature plasma: **1**, 10
Arresters: **6**, 90
Automatic compensation: **6**, 141
Automatic voltage regulator: **5**, 35
Automation: **8**, 16

Balanced current reactor: **6**, 102
Basic design: **4**, 11
Bidirectional signal current-resonant switch: **1**, 119
Bonded magnet: **1**, 34
Branch line: **8**, 50
Branch load: **8**, 37
Breakthrough: **2**, 13
Brushless exciterless scheme: **8**, 101
Brushless excitation scheme. **2**: 102
Brushless motor: **6**, 122
Brushless synchronous generator: **7**, 135
Brushless synchronous motor: **3**, 91
Brushless three-phase synchronous motor: **2**, 102
Bow-tie tree: **5**, 59
Boundary thermal resistance: **4**, 25
Bundle conductor: **6**, 61
Bypass method: **6**, 17

Cable-in-conduit conductors: **5**, 24
Calibration method: **4**, 54
Carbon dioxide (CO_2) emission reduction: **6**, 35
Ceramic sensor: **1**, 52
Characteristics analysis: **3**, 91
Charging: **2**, 1
Choke coil: **1**, 26
Circuit quality: **8**, 84
Circular spline: **7**, 114
Cognitive science: **4**, 33
Colorimetric analysis: **5**, 44
Combined levitation and guidance system: **3**, 123
Commutation failure phenomenon: **2**, 40
Commutation failure prevention control: **2**, 40
Compact synchrotron light source: **7**, 95
Compensation: **3**, 65
Compensation of stator resistance: **1**, 98
Compensation permanent magnet: **4**, 135
Conduction angle control: **3**, 103
Constant voltage: **4**, 123
Contact failure: **2**, 53
Contact-opening phase control: **5**, 14
Core loss: **7**, 1
Core moving type: **6**, 132
Coreless motor: **6**, 122
Creepage discharge: **2**, 116
Cross-country multifault analysis: **6**, 48
Cross-linked polyethylene: **8**, 1
Current control method: **5**, 93
Cycloconverter: **3**, 111
Cylindrical linear pulse motor: **4**, 125

Damper: **2**, 120
DC component: **6**, 17
Dc voltage control: **5**, 1
Dc/dc converter: **1**, 119, 134; **7**, 126
Decentralized control: **1**, 43; **7**, 73
Decentralized power plants: **7**, 85
Detectable maximum magnetic field: **1**, 60
Deterioration diagnosis: **5**, 44
Diagnosis: **2**, 53; **7**, 23
Dielectric breakdown: **8**, 59
Dielectric breakdown strength: **8**, 1
Digital filter: **2**, 29; **7**, 38
Digital protective relay: **7**, 38
Digital signal processor: **2**, 29
Dimensions of cores: **3**, 9
Direct drive motor: **6**, 141
Direct power generation: **3**, 46
Discharge: **7**, 11
Distortion factor: **8**, 116

Electrical Engineering in Japan

Subject Index to Volume 113, 1993

Ablation arc: **1**, 1
Ablation drag: **1**, 10
AC exciting synchronous generator: **1**, 70
AC superconducting stranded conductor: **4**, 25
Acceleration control: **5**, 102
Accelerator: **8**, 136
AC/DC system: **2**, 40
Active filter: **3**, 135
Adjustable speed hydroelectric power generation: **1**, 70
AE sensor: **8**, 73
Air-gap flux: **4**, 101; **5**, 35
Alkali metal **3**: 45
β″-Alumina: **3**, 46
Anti-resonance: **2**, 91
Application: **2**, 13
Approximation of magnetic characteristics: **6**, 1
Arc voltage **3**: 27
Arcing: **2**, 53
Arcing in polyethelene: **1**, 1
Armature: **1**, 10
Armature plasma: **1**, 10
Arresters: **6**, 90
Automatic compensation: **6**, 141
Automatic voltage regulator: **5**, 35
Automation: **8**, 16

Balanced current reactor: **6**, 102
Basic design: **4**, 11
Bidirectional signal current-resonant switch: **1**, 119
Bonded magnet: **1**, 34
Branch line: **8**, 50
Branch load: **8**, 37
Breakthrough: **2**, 13
Brushless exciterless scheme: **8**, 101
Brushless excitation scheme. **2**: 102
Brushless motor: **6**, 122
Brushless synchronous generator: **7**, 135
Brushless synchronous motor: **3**, 91
Brushless three-phase synchronous motor: **2**, 102
Bow-tie tree: **5**, 59
Boundary thermal resistance: **4**, 25
Bundle conductor: **6**, 61
Bypass method: **6**, 17

Cable-in-conduit conductors: **5**, 24
Calibration method: **4**, 54
Carbon dioxide (CO_2) emission reduction: **6**, 35
Ceramic sensor: **1**, 52
Characteristics analysis: **3**, 91
Charging: **2**, 1
Choke coil: **1**, 26
Circuit quality: **8**, 84
Circular spline: **7**, 114
Cognitive science: **4**, 33
Colorimetric analysis: **5**, 44
Combined levitation and guidance system: **3**, 123
Commutation failure phenomenon: **2**, 40
Commutation failure prevention control: **2**, 40
Compact synchrotron light source: **7**, 95
Compensation: **3**, 65
Compensation of stator resistance: **1**, 98
Compensation permanent magnet: **4**, 135
Conduction angle control: **3**, 103
Constant voltage: **4**, 123
Contact failure: **2**, 53
Contact-opening phase control: **5**, 14
Core loss: **7**, 1
Core moving type: **6**, 132
Coreless motor: **6**, 122
Creepage discharge: **2**, 116
Cross-country multifault analysis: **6**, 48
Cross-linked polyethylene: **8**, 1
Current control method: **5**, 93
Cycloconverter: **3**, 111
Cylindrical linear pulse motor: **4**, 125

Damper: **2**, 120
DC component: **6**, 17
Dc voltage control: **5**, 1
Dc/dc converter: **1**, 119, 134; **7**, 126
Decentralized control: **1**, 43; **7**, 73
Decentralized power plants: **7**, 85
Detectable maximum magnetic field: **1**, 60
Deterioration diagnosis: **5**, 44
Diagnosis: **2**, 53; **7**, 23
Dielectric breakdown: **8**, 59
Dielectric breakdown strength: **8**, 1
Digital filter: **2**, 29; **7**, 38
Digital protective relay: **7**, 38
Digital signal processor: **2**, 29
Dimensions of cores: **3**, 9
Direct drive motor: **6**, 141
Direct power generation: **3**, 46
Discharge: **7**, 11
Distortion factor: **8**, 116

Distributed functions: **7**, 38
Distribution line: **6**, 90
Disturbance observer: **6**, 122
Double-circuit transmission line: **6**, 48
Double H-coil method: **6**, 1
DSP: **7**, 38; **8**, 116
Dual voltage converter: **3**, 103
Dynamic stability: **3**, 36; **6**, 71

Earth's magnetism: **1**, 60
Economics of scale: **7**, 85
EDS maglev vehicle: **3**, 123
Electromagnetic attractive force: **6**, 61
Electromagnetic field analysis: **4**, 11
Electron-bean wobbling method: **7**, 95
Elliptic deformation: **7**, 114
EML: **1**, 10
Energy efficiency: **6**, 35
Energy integration: **4**, 54
Energy savings: **6**, 35
Energy system model: **6**, 35
Epoxy impregnation: **4**, 25
Epoxy resins: **3**, 17
Estimation: **7**, 61
Equivalent noise voltage: **5**, 127
Evaluation function: **5**, 127
Excitation by discharge current of capacitor: **8**, 137
Excitation control: **3**, 36
Exciting current adjustment: **4**, 135

Faraday effect: **8**, 50
Fast sampling: **7**, 38
Fault location: **3**, 27
Fault section detection: **8**, 50
Feasibility: **2**, 13
Fe-Cu-Nb-Si-B-X: **1**, 26
Fe-Cu-Nb-X-B: **1**, 26
Feedforward control: **4**, 113
Ferrite: **1**, 52
Fe-Zr-B alloy: **7**, 1
FFT: **3**, 135
Field acceleration method (FAM): **3**, 79
Field-coordinated oriented control of thrust force: **8**, 127
FINEMET: **1**, 26
Finite element method: **3**, 91; **7**, 135
Flashover characteristics: **7**, 11
Flexspline: **7**, 114
Fluctuating load: **5**, 114
Flux control: **2**, 65
Flux observer: **1**, 109
Flux pulsation: **2**, 121
Flux synthesizing linear induction motor (FSLIM): **8**, 116

Force transmission mechanism: **5**, 102
Forced flow: **5**, 24
Forward and flyback hybrid transformer: **1**, 119
Fourier series: **8**, 93
Fourier series expansion: **6**, 141
Frequency fluctuation: **4**, 78
Frictional force: **7**, 114
Full-wave rectifier circuit: **8**, 101
Fully superconducting generator: **3**, 36

Gas circuit breaker: **5**, 14
Gas-insulated switch gear (GIS): **2**, 53
Gas insulation: **7**, 11
Gas mixtures: **7**, 11
Generator: **2**, 80; **6**, 11
Generator out of synchronism: **8**, 37
Generator shedding: **7**, 61
Ground fault: No **2**, 53; **8**, 50
GTO inverter: **1**, 80
Guided light discharge: **4**, 66

Half-wave rectifier: **7**, 135
Harmonic analysis: **3**, 27; **8**, 93
Harmonic flux: **2**, 112
Harmonics: **2**, 91, 121; **3**, 135; **5**, 127
Heat engine: **3**, 46
High-frequency extinction of arc: **5**, 14
High-frequency inverter: **6**, 114
High-frequency link: **1**, 119; **3**, 111
High-frequency magnetic properties: **3**, 1
High power factor: **5**, 83
High-sensitivity magnetic field sensor: **1**, 60
High silicon: **3**. 1
High-speed sampling: **2**, 29
Hunting phenomenon: **5**, 35
HVDC: **5**, 1
Hypertext: **4**, 33

Impedance method: **3**, 27
Induced lightning: **6**, 90
Inductance: **2**, 65
Induction generator: **5**, 71
Induction motor: **3**, 65, 79; **5**, 114
Induction motor model: **6**, 81
Inrush current: **5**, 71
Inset permanent magnet type: **4**, 135
Instantaneous interruption: **8**, 84
Instantaneous power: **4**, 113
Instantaneous value symmetrical components: **5**, 71
Insulating paper deterioration: **5**, 44
Insulation against lightning: **6**, 90
Insulation characteristics: **5**, 59
Insulation deterioration: **3**, 17
Insulation diagnosis: **3**, 17; **6**, 17; **8**, 16, 59
Insulation diagnosis in live condition: **4**, 46

Interconnecting power system: **8**, 37
Inverse excitation: **1**, 60
Iron loss: **3**, 1

Jumping ring: **8**, 136

500-kV transmission lines: **7**, 52

Large-scale power system: **1**, 43
Laser: **4**, 66
LC filter: **2**, 90
LC tuned filter: **3**, 136
Leading branch load power factor: **8**, 37
Leakage inductance: **3**, 65
Length in the traveling direction: **2**, 112
Levitation coil: **2**, 112
Levitation coil design: **3**, 123
Life exponent: **5**, 59
Life test: **3**, 17
Lightning: **4**, 66
Lightning-shielding: **4**, 66
Linear activator: **8**, 136
Linear dc motor: **6**, 122
Linear induction motor (LIM): **8**, 127
Linear oscillatory actuator: **6**, 132
Linear programming: **7**, 74
Live-line measurement: **8**, 59
Location: **8**, 16
Long-term aging test: **5**, 59
Long wavefront switching voltage: **8**, 26

Magnetic application: **1**, 26
Magnetic characteristics of oriented silicon steel: **6**, 1
Magnetic field analysis: **1**, 70; **7**, 135
Magnetic fluid: **2**, 65
Magnetic levitation (MAGLEV) systems: **3**, 123
Magnetic material: **1**, 26
Magnetic noise: **5**, 127
Magnetic properties: **1**, 34
Magnetic properties of cores: **3**, 9
Magnetic semiconductor: **1**, 52
Magnetically anisotropic: **2**, 121
Magnetically levitated train: **2**, 112
Magnitomotive force: **4**, 101
Measurement: **7**, 61
Melt-spun ribbon: **12**, 34
Microscopic cones: **1**, 18
Mist: **7**, 11
Motion of ring: **8**, 136
MRAS application: **1**, 98
Multilayer piezoelectric device: **7**, 114
Multiple-degrees-of-freedom system: **5**, 102
Multiple-function armature winding design: **2**, 102
Multiple transformer: **1**, 80
Multiprocessor: **7**, 38
Multiterminal (HVDC transmission): **5**, 1

Nanocrystalline materials: **7**, 1
Nanocrystalline soft magnetic material: **1**, 26
Nd-Pr-Fe-Co-B-V alloy system: **1**, 34
Network motion system: **5**, 102
Neural network: **6**, 71
Neutral-point-clamped voltage-source inverter: **5**, 93
Neutral-point potential: **5**, 93
Nine-phase inverter: **6**, 102
Noise: **4**, 23
Noise current: **6**, 17
Noise reduction: **5**, 127
Normal zone propagation: **5**, 24

Object-oriented system: **4**, 33
Observer: **3**, 36
Occurrence region: **8**, 37
Oil-immersed transformers: **5**, 44
On-line deterioration diagnosis: **6**, 17
On-line extension angle estimation: **2**, 40
Operating time delay: **1**, 43
Optical fiber **8**: 84
Optical magnetic field sensor: **8**, 50
Optimal pulse pattern: **6**, 102
Optimal regulator technique: **8**, 116
Optimization: **2**, 112
Order-disorder phase transitions: **3**, 1
Ordering: **3**, 56
Organic insulating material: **3**, 17
Orthogonal magnetic field: **2**, 65
Output filter: **8**, 93
Overhead ground wire: **6**, 90
Overheat: **2**, 53

PAM: **5**, 127
PAM inverter: **7**, 126
Parallel processing: **3**, 56
Parallel running in system: **5**, 71
Parallel running phase angle: **5**, 71
Partial discharge: **2**, 1; **3**, 17; **4**, 46; **7**, 23; **8**, 16, 59, 73
Partial discharge measurement: **3**, 17
Permanent magnet: **2**, 65; **3**, 91
Permeance: **4**, 101
Permendur: **6**, 132
Phase decoupling: **3**, 79
Photovoltaic power generation: **4**, 54
Pipe jumper: **7**, 52
Plasma: **4**, 66
Plasma armature: **1**, 10
Plasma leakage: **1**. 10
Polytetrafluoroethylene (PTFE): **1**, 18
Power apparatus: **2**, 80
Power cable: **8**, 16

Power flow reversal control: **5**, 1
Power-frequency characteristics: **4**, 78
Power plant planning: **7**, 85
Power source: **2**, 80
Power system: **7**, 61, 74
Power system control: **7**, 38
Power system measurement and control: **2**, 29
Power system phenomena: **4**, 23
Power system requirements: **2**, 13
Power system stabilization: **2**, 80
Power system stabilizer (PSS): **4**, 1
Prediction: **7**, 61
Prefabricated joints: **4**, 46; **8**, 73
Preview control: **6**, 122
Pulsewidth modulation: **5**, 83
PWM: **5**, 127
PWM control: **1**, 134
PWM inverter: **4**, 113; **6**, 102, **7**, 126
PWM rectifier: **4**, 113

Quench: **5**, 24
Φ-Q pattern, **4**, 46
Q-value: **3**, 135

Random signals: **4**, 78
Railgun: **2**, 10
Reactive power compensator: **1**, 80
Real time: **7**, 61
Rectifier: **2**, 80; **5**, 83
Redeposition: **1**, 18
Reignition of arc: **5**, 14
Repetitive learning control: **5**, 114
Rod horn: **7**, 52
Rotor resistance: **3**, 65
S-matrix method: **6**, 71
Sampling: **4**, 54
Saturable reactor: **1**, 134
Secondary excitation of induction generator: **4**, 123
Security: **7**, 74
Self-commutated converter: **5**, 1
Self-excited induction generator: **4**, 123
Self-organizing feature maps: **6**, 71
Semiconducting layer interface: **8**, 1
Semiconductor protector: **1**, 52
Separately commutated inverter control: **4**, 123
Separately controlled PFM strategy: **1**, 119
Series active filter: **2**, 91
Series exciting: **8**, 101
Series multiplexing: **5**, 93
SF6 gas: **2**, 1
Short-circuit current: **6**, 61
Short-circuit distance relay: **6**, 48
Shunt reactor: **5**, 14
Silicon steel: **3**, 1
Simulation: **7**, 23
Simulator: **4**, 33
Single-ended topology. **1**: 119
Single-phase rectifier: **7**, 106; **8**, 93
Single sheet tester of rotational losses: **6**, 123
Single-terminal operation: **5**, 1
Sinusoidal wave output: **7**, 126
Skin effect: **2**, 121
Small hydraulic power generator: **5**, 71
Small lagging current interruption: **5**, 14
Smoothing capacitor: **7**, 106
Sodium: **3**, 46
Soft magnetic properties: **7**. 1
Soft switching: **1**, 134; **6**, 114
Solid electrolyte: **3**, 46
Soliton: **5**, 102
Space harmonic magnetic field: **8**, 101
Space vector: **3**, 79
Spacer interval: **6**, 61
Sparse matrix: **3**, 56
Spectral analysis: **4**, 78
Speed estimation: **1**, 98
Speed sensorless control: **1**, 98, 109
Sputter etching: **1**, 18
Stability margin: **5**, 24
Stability of MRAS: **1**, 109
Stabilizing control: **4**, 89
Stabilizing control system: **7**, 61
State feedback: **3**, 36
Static thrust: **6**, 132
Statistical estimation method: **6**, 17
Step-up/down voltage: **5**, 83
Stochastic programming problem: **7**, 85
Strain assemblies: **7**, 52
Strain-wave gearing: **7**, 114
Stress relief cone: **8**, 73
Structure analysis: **1**, 34
Switching loss: **7**, 126
Substation insulator: **8**, 26
Superconducting generator: **4**, 11
Super multiphase switching: **8**, 127
Superconducting magnet: **2**, 112; **7**, 95
Superconducting magnetic energy storage unit: **4**, 1
Superconductivity: **2**, 13
Superconductors: **5**, 24
Superstructure: **8**, 1
Suppression of speed variation: **5**, 114
SWEEP method: **1**, 43
Switching: **8**, 84
Synchronous generators: **4**, 101; **5**, 35
System monitoring: **4**, 54
System interconnection: **4**, 1
System stabilizing control: **4**, 1

Tape-wound toroidal core: **3**, 9
Temperature distribution of arc discharge: **1**, 1
Temporary ac withstand voltage: **8**, 26
Tension: **6**, 61
Thermal aging: **8**, 1
Thermal conduction: **4**, 25
Thermoelectric conversion: **3**, 46
Thickness: **3**, 1
Three-phase synchronous generator: **8**, 101
Thrust unbalance: **4**, 135
Torque control: **3**, 65
Torque observer: **6**, 141
Torque ripple: **6**, 141
Training system: **4**, 33
Transfer function: **4**, 78
Transformer: **1**, 26
Transient analysis: **6**, 81
Transient analysis factorization: **3**, 56
Transient stability: **7**, 61
Triple three-phase winding: **6**, 102
Two-component network: **6**, 48
Two-quadrant chopper: **7**, 106
Two-stage dc voltage control: **5**, 1
Two-terminal (HVDC transmission): **5**, 1
Uncertainty of demand: **7**, 85
Unbalanced load: **4**, 101
Uninterruptible power supply: **3**, 111
Unity power factor: **3**, 103

Variable impedance power system: **4**, 89
Variable series capacitor system: **4**, 89
Vector control: **3**, 65, 79
Voltage clamped: **3**, 111
Voltage collapse: **6**, 81
Voltage compensation: **3**, 135
Voltage control: **1**, 43
Voltage integral control method: **7**, 106
Voltage margin: **5**, 1
Voltage phase angle: **7**, 61
Voltage-source inverter: **5**, 127
Voltage-source PWM converter: **8**, 116
Voltage source-type converter: **5**, 1
Voltage stability: **6**, 81
Voltage waveform distortion: **1**, 70
V-t characteristics: **5**, 59

Water tree: **6**, 17
Wave frequency analysis. **3**: 27
Waveform compensation circuit: **6**, 1
Waveform improvement: **5**, 127; **6**, 102
Wedge: **2**, 121
Wedge gap: **2**, 1
Weibull statistics: **5**, 59

XLPE cable line: **8**, 59
X-ray lithography: **7**, 95

Y-branch joint box: **8**, 50
Yoke coil: **8**, 59

ZCS rectifier diode: **1**, 119
Zero-current soft switching (ZCS): **1**, 119
Zero current switching: **6**, 114
Zero magnetic field: **1**, 60
Zero-power flow phenomenon: **8**, 37
Zero voltage switching: **6**, 114